

# CARE & MAINTENANCE GUIDE

Your new Invisi-Gard® Stainless Steel Security Screens have been manufactured using the highest quality materials available to the security screening industry. Constructed from Marine Grade 316 Stainless Steel Mesh and architectural aluminium extrusion. Both metals are highly corrosion resistant and exceptionally strong, with a moderate amount of maintenance, your Invisi-Gard® Stainless Steel Security Screens will retain their good looks and resist the elements for years to come.

Invisi-Gard® Stainless Steel Security Screens are the product of years of development and are designed to resist corrosion and rusting, but as with all external fixtures on

your home, they require some maintenance to keep looking good and performing well. Depending on how harsh the environmental elements are, the maintenance period will vary. Refer to the suggested maintenance table.

Your Invisi-Gard® Stainless Steel Security Screens should only be washed down with the highly recommended Wash & Wax kit a soft bristled brush and mains water only.

Ensure you rinse well to remove any residue from the mesh surface.

Bore or tank water should never be used as it is unacceptable and may lead to detrimental corrosion.

Strong detergents and abrasive cleaners must also never be used to clean your Invisi-Gard® Stainless Steel Security Screens as these may scratch or damage the surface finish and increase the likelihood of corrosion.

Lubrication of the locking components should be carried out periodically to ensure smooth operation.

## SUGGESTED MAINTENANCE PERIOD TABLE

Environment	Recommended Maximum Maintenance Interval*
<b>Mild</b> <i>Greater than 10km radius from oceanfront or saline bay</i>	<b>Every 6 months</b>
<b>Moderate</b> <i>Within 1km to 10km radius of an oceanfront or saline bay</i>	<b>Every 2 to 3 months</b>
<b>Marine</b> <i>Within 500m to 1km radius of an oceanfront or saline bay</i>	<b>Every 2 to 4 weeks</b>
<b>Severe Marine</b> <i>Within 500m radius of an oceanfront or saline bay</i>	<b>Every 1 to 2 weeks</b>

\* Indicative maintenance schedule only.

External contaminants that come into contact with the Invisi-Gard® screens such as bird and bat droppings are very acidic and can quickly burn and damage the powder coat finish of the frame and the mesh coating. To ensure the Invisi-Gard® warranty is maintained, it is essential that these external contaminants are cleaned as soon as possible.

